

# EX2

## TRADITIONAL ESPRESSO

EX2

### Versions

- EX2 MINI 1GR CONTROL
- EX2 MINI 2GR CONTROL
- EX2 2GR CONTROL

# EX2

### Features



EX2 perfectly combines the heritage from CREM traditional espresso machines with a contemporary design within the EX line.

Its optimized but robust body includes Expobar well known reliable and consistent hydraulics to offer a wide range of espresso-based drinks. The EX2 is, in this sense, the best choice for those businesses looking for a smart balance between budget and performance.

The EX2 comes in three versions -**2gr, Mini 2gr and Mini 1gr**- to suit any kind of sites.

### Main USP's

- Optimized and robust design line
- Expobar well known reliable hydraulics
- 1/2 rotatory knobs
- Electronic pre-infusion and pre-infusion chamber group head
- Ergonomics & Barista flow
- Improved cup tray area
- Ease-of-servicing

CREM*Tech*  
inside

### Options & Extras

- Take away versions
- Barista lights
- Extra steam wand for 2GR versions




## Technical specifications



	EX2 2GR	EX2 MINI 2GR	EX2 MINI 1GR
<b>Height, width, depth</b>	460, 735, 575 mm	460, 515, 575 mm	460, 515, 575 mm
<b>Weight</b>	57 Kg	48 Kg	45 Kg
<b>Power ratings</b> <i>(Power ratings+OPTIONS)</i>	220-240V 1N~ 3350W 50-60Hz	220-240V 1N~ 2800W 50-60Hz	220-240V 1N~ 2800W 50-60Hz
<b>Boiler(s) capacity</b>	11.5 l	6 l	6 l
<b>Operation pressure</b>	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar
<b>Pressure switch control</b>	✓	✓	✓
<b>PID control</b>	-	-	-
<b>Water connection</b>	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread
<b>Height group</b>	STD / TA (O)	STD / TA (O)	STD / TA (O)
<b>Volumetric dosing (5 keypad button)</b>	✓	✓	✓
<b>Volumetric dosing + group display</b>	-	-	-
<b>Group flush button</b>	✓	✓	✓
<b>Steam wands + HW tap</b>	1+1	1+1	1+1
<b>Extra steam wand</b>	O	-	-
<b>Auto hot tap water dose</b>	O	-	-
<b>½ turn rotary taps</b>	✓	✓	✓
<b>Lever taps</b>	-	-	-
<b>Cool touch steam wands</b>	-	-	-
<b>Built-in rotatory pump</b>	✓	✓	✓
<b>Pre infusion chamber group head</b>	✓	✓	✓
<b>Electronic pre infusion</b>	✓	✓	✓
<b>Jet hole</b>	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm
<b>Pressure gauge</b>	60 mm single	60 mm single	60 mm single
<b>High feet / Hidden feet</b>	-	-	-
<b>Colours</b>	Light grey	Light grey	Light grey
<b>Knob finishing</b>	Black	Black	Black
<b>Body covers</b>	-	-	-
<b>Barista lights</b>	O	O	O
<b>Auto cleaning group cycle</b>	✓	✓	✓
<b>ECO mode</b>	-	-	-
<b>Auto On/OFF</b>	-	-	-
<b>Optional power cord (Country Kit)</b>	STD: Type F (1Ph) O: 1Ph (Type I AUS 15A, 16A BareW)	STD: Type F O: 1Ph (Type I AUS 10A, Type G 13A)	STD: Type F O: 1Ph (Type I AUS 10A, Type G 13A)
<b>Single+Double portafilter</b>	1+1	1+1	1+1
<b>Extra portafilters</b>	-	-	-

**NOTE:** Please check your regional price list for available versions/options and part numbers.

**INSTALLATION NOTE:** Please refer to the User Manual and the Technical Manual.



Welbilt reserves the right to make changes to the design or specifications without prior notice.